

# Ergo-lift

New!

Pneumatic wheel lift



*Just right !*

*Lighten your workload !*



## SIZE APPLICABLE

- For all types of passenger car, van and light vehicle wheels
- Maximum tyre width : 36 cm
- Maximum Rim width 13"
- Maximum wheel weight : 60kg
- Lifts the wheel at the height of : 76 cm

## SPECIFICATIONS

- Working air pressure : 7 bar
- Length : 79/60cm
- Width : 61 cm
- Height : 39/96 cm
- Weight : 26 kg
- Standard colour : red RAL 3020

## OPTIONS

- RAL colour on request
- Customized adaptations



**DQN - DU QUESNE**

Quellinstraat 42  
B-2018 Antwerp  
Belgium

+32 3 201 51 10

[info@dqn.be](mailto:info@dqn.be)

[www.dqn.be](http://www.dqn.be)





The Ergo-lift is the first link in the brand new "Ergo-line" chain. This small automatic wheel lift can load your "Ergo-roll" roller conveyer at a lightening pace or bring the wheel to the load height of all DQN products.

Indeed, two configurations are possible: in the "Ergo-roll table load" mode, the lifting movement rises to its maximum height without braking, providing the wheel with horizontal speed so that it moves forward on the roller table. The speed is adjustable according to the distance it must travel on the table. In the "Machine load" mode the movement stops at loading height and stays at a high position as long as the wheel has not been unloaded.

The self-activating lift starts to operate as soon as a wheel is placed on it and goes down as soon as it is unloaded.

Its semi-circular movement offers the great advantage of moving the wheels from a vertical position (on the ground) to a horizontal position (at work height) without any jolt or fall.

Its unique compact structure allows for it to be taken outside the handling area once the wheel is unloaded. (height at rest 39cm)

Ergo-line *New!*



**SEE ALSO**

Ergo-roll *New!*

Ergo-press *New!*

*Opti-fit*

*Pro-fit*

*Manu-fit*

